

**Tyre VF650/50R22.5 AR838 Steel Belt Advance 165D TL (ž/ū)**

|                                   |                    |
|-----------------------------------|--------------------|
| Category                          | Agricultural tyres |
| Size                              | VF650/50R22.5      |
| Model                             | AR838 Steel Belt   |
| Ply                               |                    |
| Load ind. (LI)                    | 165                |
| Speed ind. (SI)                   | D                  |
| Maximum load per tire, kg         | 5150               |
| Maximum speed, km/h               | 65                 |
| Inflation pressure, atm           | 2.8                |
| Analogue                          |                    |
| Outer diameter (OD), mm           | 1235               |
| Section Width (SW), mm            | 645                |
| Dynamic rolling circumference, mm | 3650               |
| Static Loaded Radius, mm          | 554                |
| Recomend/permitted rim            | 20                 |
| Radial/ bias                      | Radial             |
| Origin                            | China              |
| TT / TL                           | TL                 |
| Set                               | TL                 |

|          |         |
|----------|---------|
| Delivery | 1-5 w/d |
|----------|---------|

|          |  |
|----------|--|
| Warranty |  |
|----------|--|

|             |  |
|-------------|--|
| Description |  |
|-------------|--|

All technical information about products in our website protekta.lt is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.