

## Tyre 26x12.00-12 I3D Advance 10PR 124A2 TL

|             |         |                          |                    |
|-------------|---------|--------------------------|--------------------|
| Delivery    | 1-5 w/d | Category                 | Agricultural tyres |
|             |         | Size                     | 26x12.00-12        |
| Warranty    |         | Model                    | I3D                |
|             |         | Ply                      | 10                 |
|             |         | Load ind. (LI)           | 124                |
|             |         | Speed ind. (SI)          | A2                 |
|             |         | Maximum load per tire,   | 1630               |
|             |         | kg                       |                    |
|             |         | Maximum speed, km/h      | 10                 |
|             |         | Inflation pressure, atm  | 4.5                |
|             |         | Analog                   |                    |
|             |         | Outer diameter (OD), mm  | 648                |
|             |         | Section Width (SW), mm   | 307                |
|             |         | Dynamic rolling          | 1875               |
|             |         | circumference, mm        |                    |
|             |         | Static Loaded Radius, mm | 291                |
|             |         | Recomend/permitted rim   | 10.50              |
|             |         | Radial/ bias             | Bias               |
| Description |         | Origin                   | China              |
|             |         | TT / TL                  | TL                 |
|             |         | Set                      | TL                 |

All technical information about products in our website protekta.lt is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.