

## Tyre 540/65R30 AR1200 Steel Belt Advance 150D TL

|             |     |                                   |                    |
|-------------|-----|-----------------------------------|--------------------|
| Delivery    | --- | Category                          | Agricultural tyres |
| Warranty    |     | Size                              | 540/65R30          |
|             |     | Model                             | AR1200             |
|             |     | Ply                               |                    |
|             |     | Load ind. (LI)                    | 150                |
|             |     | Speed ind. (SI)                   | D                  |
|             |     | Maximum load per tire, kg         |                    |
|             |     | Maximum speed, km/h               |                    |
|             |     | Inflation pressure, atm           |                    |
|             |     | Analog                            |                    |
|             |     | Outer diameter (OD), mm           |                    |
|             |     | Section Width (SW), mm            |                    |
|             |     | Dynamic rolling circumference, mm |                    |
|             |     | Static Loaded Radius, mm          |                    |
|             |     | Recomend/permited rim             |                    |
|             |     | Radial/ bias                      | Radial             |
|             |     | Origin                            | China              |
|             |     | TT / TL                           | TL                 |
|             |     | Set                               | TL                 |
| Description |     |                                   |                    |

All technical information about products in our website protekta.It is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.