

**Tyre 15.5/80-24 (400/80-24) TA60 Petlas 12PR 157/145A6 TL**

|                                   |                    |
|-----------------------------------|--------------------|
| Category                          | Agricultural tyres |
| Size                              | 15.5/80-24         |
| Model                             | TA60               |
| Ply                               | 12                 |
| Load ind. (LI)                    | 157 / 145          |
| Speed ind. (SI)                   | A6                 |
| Maximum load per tire, kg         | 4125 / 2900        |
| Maximum speed, km/h               | 30                 |
| Inflation pressure, atm           | 2.9                |
| Analogue                          | 400/80-24          |
| Outer diameter (OD), mm           | 1262               |
| Section Width (SW), mm            | 394                |
| Dynamic rolling circumference, mm | 3660               |
| Static Loaded Radius, mm          | 573                |
| Recomend/permitted rim            | W12; W13, W14L     |
| Radial/ bias                      | Bias               |
| Origin                            | Turkey             |
| TT / TL                           | TL                 |
| Set                               | TL                 |

|             |           |
|-------------|-----------|
| Delivery    | ---       |
| Warranty    | 60 months |
| Description |           |

All technical information about products in our website protekta.lt is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.