

## Tyre 12-16.5 L4A Advance 12PR 144A2 TL

|             |         |                                      |                  |
|-------------|---------|--------------------------------------|------------------|
| Delivery    | 1-5 w/d | Category                             | Industrial tyres |
| Warranty    |         | Size                                 | 12-16.5          |
|             |         | Model                                | L4A              |
|             |         | Ply                                  |                  |
|             |         | Load ind. (LI)                       | 144              |
|             |         | Speed ind. (SI)                      | A2               |
|             |         | Maximum load per tire,<br>kg         | 2850             |
|             |         | Maximum speed, km/h                  | 10               |
|             |         | Inflation pressure, atm              | 5.5              |
|             |         | Analog                               |                  |
|             |         | Recomend/permitted rim               | 9.75             |
|             |         | Radial/ bias                         | Bias             |
|             |         | Outer diameter (OD), mm              | 831              |
|             |         | Section Width (SW), mm               | 307              |
|             |         | Static Loaded Radius, mm             |                  |
|             |         | Dynamic rolling<br>circumference, mm |                  |
|             |         | TT / TL                              | TL               |
|             |         | Set                                  | TL               |
| Description |         |                                      |                  |

All technical information about products in our website protekta.It is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.