

**Tyre 1300-530-533 (530/70-21) E2G Advance 12PR 156B TTF**

|                                   |                  |
|-----------------------------------|------------------|
| Category                          | Industrial tyres |
| Size                              | 1300-530-533     |
| Model                             | E2G              |
| Ply                               | 12               |
| Load ind. (LI)                    | 156              |
| Speed ind. (SI)                   | B                |
| Maximum load per tire, kg         | 4000             |
| Maximum speed, km/h               | 50               |
| Inflation pressure, atm           | 3.9              |
| Analog                            | 530/70-21        |
| Recomend/permitted rim            | 440-533          |
| Radial/ bias                      | Bias             |
| Outer diameter (OD), mm           | 1300             |
| Section Width (SW), mm            | 530              |
| Static Loaded Radius, mm          |                  |
| Dynamic rolling circumference, mm |                  |
| TT / TL                           | TT               |
| Set                               | tyre+tube+flap   |

|          |         |
|----------|---------|
| Delivery | 1-5 w/d |
|----------|---------|

|          |  |
|----------|--|
| Warranty |  |
|----------|--|

|             |  |
|-------------|--|
| Description |  |
|-------------|--|

All technical information about products in our website protekta.lt is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.