

**Tyre 385/95R25 (14.00R25) GLB05 \*\*\* Advance 170F TL**

|                                   |                  |
|-----------------------------------|------------------|
| Category                          | Industrial tyres |
| Size                              | 385/95R25        |
| Model                             | GLB05 ***        |
| Ply                               |                  |
| Load ind. (LI)                    | 170              |
| Speed ind. (SI)                   | F                |
| Maximum load per tire, kg         | 6000             |
| Maximum speed, km/h               | 80               |
| Inflation pressure, atm           | 8.9              |
| Analogue                          |                  |
| Recommend/permitted rim           | 10.00            |
| Radial/ bias                      | Radial           |
| Outer diameter (OD), mm           | 1365             |
| Section Width (SW), mm            | 385              |
| Static Loaded Radius, mm          |                  |
| Dynamic rolling circumference, mm |                  |
| TT / TL                           | TL               |
| Set                               |                  |

|          |         |
|----------|---------|
| Delivery | 1-5 w/d |
|----------|---------|

|          |  |
|----------|--|
| Warranty |  |
|----------|--|

|             |  |
|-------------|--|
| Description |  |
|-------------|--|

All technical information about products in our website protekta.lt is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.