

## Tyre 13R22.5 GCD1 Advance 20PR 156/150K TL M+S 3PMSF



|                                   |                   |
|-----------------------------------|-------------------|
| Category                          | Truck & Bus tyres |
| Size                              | 13R22.5           |
| Axle                              | Rear              |
| Season                            | M+S 3PMSF         |
| Model                             | GCD1              |
| Ply                               | 20                |
| Load ind. (LI)                    | 156 / 150         |
| Speed ind. (SI)                   | K                 |
| Maximum load per tire, kg         | 4000 / 3350       |
| Maximum speed, km/h               | 110               |
| Inflation pressure, atm           | 8.64              |
| Analogue                          |                   |
| Recommend/permitted rim           | 9.75; 9           |
| Outer diameter (OD), mm           | 1124              |
| Section Width (SW), mm            | 320               |
| Static Loaded Radius, mm          | 521               |
| Dynamic rolling circumference, mm | 3405              |
| TT / TL                           | TL                |
| Set                               | TL                |
| Rolling resistance                | D                 |
| Wet grip                          | C                 |
| External noise, dB                | 75                |

|          |           |
|----------|-----------|
| Delivery | 1-5 w/d   |
| Warranty | 24 months |

### Description

All technical information about products in our website protekta.lt is based on the information given by the manufacturers. This information serves only information purposes and it is not mandatory.