

Tyre 315/70R22.5 PW610 Primewell 18PR 154/151M TL M+S

| | |
|--------------------------------------|-------------------|
| Category | Truck & Bus tyres |
| Size | 315/70R22.5 |
| Axle | Rear |
| Season | M+S |
| Model | PW610 |
| Ply | 18 |
| Load ind. (LI) | 154 / 151 |
| Speed ind. (SI) | M |
| Maximum load per tire, kg | 3750 / 3450 |
| Maximum speed, km/h | 130 |
| Inflation pressure, atm | 8.20 |
| Analogue | |
| Recomend/permitted rim | 9.00; 9.75 |
| Outer diameter (OD), mm | 1076 |
| Section Width (SW), mm | 312 |
| Static Loaded Radius, mm | 500 |
| Dynamic rolling circumference, mm | 3282 |
| TT / TL | TL |
| Set | TL |
| Rolling resistance | |
| Wet grip | |
| External noise, dB | |

| | |
|----------|-----------|
| Delivery | --- |
| Warranty | 12 months |

Description

Visa aukščiau pateikta informacija yra gauta iš gamintojo. Turinys yra rekomendacinio pobūdžio. "Protekta" nepriima atsakomybės dėl problemų kilusių su informacijos naudojimu.